


DART

DESIGN <i>[Signature]</i>	DRAWN BY RF	DART AEROSPACE USA, INC. FAIRCHILD INTERNATIONAL AIRPORT, WA	
CHECKED <i>[Signature]</i>	APPROVED <i>[Signature]</i>	DRAWING NO. D2620	REV. B SHEET 1 OF 1
DATE 99.09.10		TITLE 206 SKIDTUBE BENDING CONTROL	SCALE 1:20
A	97.11.07	NEW ISSUE	
B	97.09.10	UPDATE FOR IN-HOUSE BENDING	

RELEASED
99.09.15 DS

SPECIFICATION CONTROL DRAWING

206 SKIDTUBE BENDING



DAMAGE TOLERANCE

1. THERE SHOULD BE NO VISIBLE WRINKLES BELOW 5.0 AFTER BENDING.
2. GOUGES UP TO 0.020 DEEP ARE ACCEPTABLE IN BENT PORTION OF THE TUBE. NO GOUGES ARE ACCEPTABLE IN THE FLAT PORTION OF THE TUBE. DEEPER GOUGES ARE ACCEPTABLE IN THE PORTION OF THE TUBE ABOVE 5.0.
3. TUBE WIDTH SHOULD BE 3.20 ± 0.200 IN THE BEND.
4. TUBE WIDTH SHOULD BE 3.200 ± 0.010 IN THE FLAT PORTION OF THE TUBE.
5. TUBE HEIGHT SHOULD BE 3.15 ± 0.200 IN THE BEND.
6. TUBE HEIGHT SHOULD BE 3.150 ± 0.010 IN THE FLAT PORTION OF THE TUBE.

NOTE: ALL DIMENSIONS ARE IN INCHES